


User Manual

Model – SC502MC SDI

1、 Introduction

SC502MC SDI is a high-quality, high-performance capture device. It supports 1 channel of video inputs with SDI connectors.

2、 Specification

Product Series Hardware Specification	
Model	SC502 N1 MC SDI
Max. FPS	30/25fps @ 1920x1080p
Recording Mode	Software Compression, Real-Time Mode
Product Photo	
Dimension	Software Compression, Real-Time Mode
Interface	Minicard (PCIe Gen2 x1)
Video Input	1 × SDI
Display Video Format	YUY2
Display Video Resolution	1920x1080p@30/25/24fps 1920x1080i@60/50fps 1280x720p@60/50fps 720x480i@60fps 720x576i@50fps

Recording Video Resolution	<p>1920x1080p@30/25/24fps 1920x1080i@60/50fps 1280x720p@60/50fps 720x480i@60fps 720x576i@50fps</p>
Audio Input	<p>SDI Embedded Audio Audio L/R (2 x RCA through wafer connector to RCA cable)</p>
Audio Format	<p>Stereo / 16-bit / 32000 ~ 48000Hz</p>
SDK	<p>VC++ / .NET / VB / V4L2</p>
System Requirement	
OS Support	<p>Windows XP / Vista / Windows 7 Linux 2.6.14 or Higher (32-bit and 64-bit)</p>

3 、 Hardware Installation

Before You proceed

Please note below precautions before any install/uninstall operations:

- ✓ ALWAYS turn off the system before hardware installation/un-installation.
- ✓ ALWAYS unplug the power cord from the wall outlet/socket before hardware installation/un-installation.
- ✓ ALWAYS touch a safely grounded object or metal object before touching the device.
- ✗ DO NOT touch any devices before the system is fully off.
- ✗ DO NOT touch any electrical and semiconductor components on the device, especially ICs on board.

4.1 Card and Driver Installation

Step 1: Turn off the system and unplug power cord from wall outlet/socket.

Step 2: Remove the computer system case cover.

Step 3: Plug capture device into an available PCIe slot on motherboard.

Step 4: After hardware installation is completed, then install the driver.

4.2 Signal Source Connection Diagram

